

Data sheet

Sheet No: BH 1.200.01
Date: July 15, 2008, Page 1 of 1

Bettis BHH & BHHF

Mating components standards

Adaptor flange

In order to simplify ordering and set forward a known standard, we are electing to standardize our holes patterns on the adaptor plate of all BHH actuators as well as the insert.

Actuators will now be supplied with bottom flange connection in accordance with ISO-5211 international standard.

The table below specifies the ISO-5211 standard that will be used for each model of actuator (for optional machining standards available please refer to the Bettis price list).

If preferred, an undrilled bottom mounting flange is also available as a no cost option. When ordering, indicate the ISO-5211 standard in the suffix of the model number, or leave blank for undrilled (e.g. BHH500F10 or BHH500).

Model	ISO 5211
BHH/F125	F5
BHH/F250	F7
BHH/F500	F10
BHH/F1000	F12
BHH/F2000	F14
BHH/F4000	F16
BHH/F8000	F25
BHH/F16000	F30

Inserts


Also note, that the removable (splined) drive-nut adapter will now be supplied unmachined to allow the customer flexibility in matching valve stem dimensions and direct-mounting if so desired.

The splined adapter will allow machining to the same ISO-5211 standard as the bottom flange, with maximum dimensions as indicated on the attached table.

For factory machining please refer to the Bettis price list.

Model	Maximum Spindel Dimension (mm)	
	Cylindrical	Square
BHH/F125	17	16
BHH/F250	25	24
BHH/F500	35	30
BHH/F1000	42	36
BHH/F2000	58	50
BHH/F4000	74	63
BHH/F8000	95	80
BHH/F16000	100	90

Dimension listed are maximum bore size allowing sufficient wall thickness to accept torque load.



BETTIS[®]

www.Bettis.com

Copyright © Emerson Process Management.

The information in this document is subject to change without notice.


EMERSON[™]
Process Management