

Data sheet

Sheet No.: GH/GHCPI 2.01 RevA

Date: September 2009

GH/GHC-Series

Performance Data – (Pneumatic)

Spring-Return Actuators GH/GHC-Series

Actuator Model	Volume Per Stroke (Cu. In.)	Maximum Operating Pressure (MOP)* (PSIG)		Approximate Weight of Actuator (Lbs.)
		GH	GHC	
GH2012-SR4	1093	150	131	415
SR3	1093	154	136	423
SR2	1093	158	140	445
SR1	1093	163	145	455
SR0	1093	168	153	460
GH3014-SR4	1515	176	155	613
SR3	1515	181	159	628
SR2	1515	187	165	643
SR1	1515	194	172	648
SR0	1515	200	182	665
GH3016-SR4	2067	133	117	634
SR3	2067	137	120	648
SR2	2067	141	125	664
SR1	2067	146	130	668
SR0	2067	154	137	685
GH4020-SR4	4157	136	118	1079
SR3	4157	140	123	1139
SR2	4157	145	128	1155
SR1	4157	152	134	1164
SR0	4157	160	142	1250
GH5024-SR4	6826	161	140	1938
SR3	6826	165	144	2003
SR2	6826	168	149	2058
SR1	6826	168	156	2053
SR0	6826	168	163	2228
GH7028-SR4	11921	181	156	3548
SR3	11921	186	161	3462
SR2	11921	192	168	3812
SR1	11921	196	173	3727
SR0	11921	196	181	3761
GH7032-SR4	15791	138	120	3855
SR3	15791	142	123	3769
SR2	15791	146	129	4119
SR1	15791	152	132	4034
SR0	15791	157	138	4051
GH8032-SR3	19550	194	169	5994
SR2	19550	200	175	5654
SR1	19550	200	182	6048
SR0	19550	200	189	6048
GH8036-SR3	25491	152	133	5994
SR2	25491	157	138	6154
SR1	25491	163	143	6548
SR0	25491	169	149	6990

Notes:

- ▲ Maximum Maximum operating volume including cavity required for calculating consumption per stroke.
- * **Maximum Operating Pressure (MOP)** – The maximum recommended pressure at which the actuator should be operated.
- Maximum Relief Valve Set Pressure (MRP)** – The maximum recommended relief pressure value set point.
MRP is calculated by multiplying MOP time 1.15
- Maximum System Pressure (MSP)** – The maximum allowable system supply pressure to which an actuator may be exposed.
MSP is calculated by multiplying MOP times 1.25



www.Bettis.com

Copyright © Emerson Process Management. The information in this document is subject to change without notice.
Updated data sheets can be obtained from our website www.bettis.com or from your nearest Valve Automation Center.
USA: +1 281 727 5300 Europe: +31 74 256 1010 Asia-Pacific: +65 6501 4600



EMERSON
Process Management