



Description:

This ELQ electric actuator option provides a varying indication of the actuator and valve position by transmitting a 4- 20 mA signal, this is proportional to the output shaft. Feedback is reversible from a 4-20mA signal to a 20-4mA signal by means of a jumper setting (3).

This option consists of an electronic card and a potentiometer fed from an external (24VDC) power supply. The card is equipped with trimmers for zero (1) and span (2) adjustment. When mounted on top of the mainboard the option is connected to the terminal compartment by internal wiring.

Construction:

The electronic card (4) is mounted on top of the mainboard (5). The potentiometer (6) is mounted in the limit switch assembly (7) and is driven by the indicator shaft (8) and an intermediate gear in the limit switch assembly. The potentiometer connector (9) is plugged in the mainboard. The mainboard is prewired to the terminal strip in the terminal compartment.

Specifications:

Input	: 15 to 30 VDC
Output	: 4 to 20 mA, with adjustable zero and span.
Temperature	: -20° to +70°C
Potentiometer	: 10KΩ; other values on request.
Voltage drop	: 2V max.
Accuracy	: 2 %

Identification:

- Factory option : Add "+ Q-PT" to the basic actuator size.
: eg. ELQ100 + Q-PT.
- Kit option : Actuator size is added to: "Kit Q-PT".
: eg. Kit Q-PT / ELQ100.

Note:

- 1) When a combination of two options is needed, both of which need a feedback potentiometer, the second plug from the double potentiometer can be used.

