

Data sheet

Sheet No.: D101, Rev. B

Date: June 2005

Hytorc XL

Actuator Operating Speeds

XL26 to XL4581

Time is shown in seconds

| Actuator Model | Operating Pressure = 80 psi (5.5 bar g) | | | |
|----------------|---|----------------|--------------------|----------------|
| | Double Acting | | Spring Return with | |
| | Opening Stroke | Closing Stroke | Opening Stroke | Closing Stroke |
| XL26 | 0.01 | 0.01 | 0.05 | 0.02 |
| XL71 | 0.03 | 0.03 | 0.09 | 0.05 |
| XL131 | 0.03 | 0.04 | 0.15 | 0.09 |
| XL186 | 0.05 | 0.06 | 0.19 | 0.12 |
| XL221 | 0.06 | 0.08 | 0.24 | 0.15 |
| XL281 | 0.20 | 0.10 | 0.10 | 0.20 |
| XL426 | 0.20 | 0.30 | 0.30 | 0.50 |
| XL681 | 0.40 | 0.60 | 0.40 | 1.20 |
| XL1126 | 0.70 | 0.60 | 0.50 | 0.70 |
| XL1371 | 0.80 | 0.70 | 0.70 | 1.00 |
| XL2586 | 1.50 | 1.20 | 1.20 | 1.50 |
| XL4581 | 2.00 | 2.90 | 2.20 | 3.90 |

www.Hytorc.com

Copyright © Emerson Process Management. The information in this document is subject to change without notice.
Updated data sheets can be obtained from our website www.hytorc.com or from your nearest Valve Automation Center
USA: +1 813 630 2255 (fax 630 9449) UK: +44 191 5180020 (fax 5180032)

**EMERSON**
Process Management